

DATA SHEET

Semi-Buried Pedestal (Type-07)

Semi-Buried Pedestal Enclosure

RLH Type-07 Semi-Buried Pedestals are tough, outdoor rated, all-dielectric equipment pedestals that include a treated plywood backboard, lockable covers with hex head self-locking system, and padlock hasp. The pedestal stands approximately 36" tall when the base is buried. No mounting stakes or platforms are required for installation.

These pedestals offer a large 30 inch wide surface for mounting telecommunications, networking or control equipment, making it ideal for high density or bulky equipment installations. Pedestals are constructed of all-dielectric, LLDPE molded plastic, with a sturdy steel support frame and ground bar.

Custom configurations with fiber, telco or networking equipment preinstalled are also available, allowing for faster and more uniform installations in the field.



Semi-Buried Pedestal (Type-07)

Key Features

- All-dielectric construction
- Internal steel frame
- Fire treated and painted 3/4" plywood backboard
- Self-locking cover with hex head release
- Spring latch and padlock locking hasp
- Ground lug connections
- 7" mounting depth on front of backboard
- 8" mounting depth on back of backboard
- Extra large mounting area to accommodate a wide range of applications
- May be customized with equipment preinstalled
- Made in USA



Open Front

Ordering Information

Description	Housing	Part Number
H48" x W36" x L24" with 3/4" Fire Retardant Plywood Backboard	Empty Backboard	8806-1285-07

DATA SHEET

www.fiber opticlink.com

Key Specifications

Construction:	GR-13 compliant all-dielectric LLDPE molded plastic with metal backboard frame
Mounting Style:	Semi-buried, 36" X 24" approximate footprint
Included:	Ground lug with attaching hardware
Options:	Custom configurations with equipment preinstalled.

Contact

By Mail: Att: Sales
RLH Industries, Inc.
936 N. Main St.
Orange, CA 92867

By Phone: Local 714-532-1672
Sales / Service
Mon - Fri, 6am - 6pm, PST Toll Free 800-877-1672
866-DO-FIBER

By Email: info@fiber opticlink.com

By FAX: 714-532-1885

Tech Support

By Email: support@fiber opticlink.com

By Phone: Toll Free 855-754-2497
855-RLH-24X7